



A Division of Thiessen Products

INSTRUCTION SHEET FOR TOOL #2043



FORK NUT SOCKET

USE ON ALL WIDE GLIDE FORK TUBE PLUGS

1. Refer to Harley Davidson® Service Manual for specifications.
2. Remove top fork nut using JIMS® #2244 socket tool.
3. Loosen bottom T-Stem pinch bolt, holding fork tube assembly.
4. Remove fork slider and tube assembly.
5. Carefully clamp tube assembly in vise, using soft jaws, so as not to damage fork tube.
6. **WARNING:** the fork tube plug is under pressure from fork spring. Be careful when removing plug to prevent bodily injury. Unscrew plug slowly, with a 1/2" drive ratchet or breaker bar while applying downward pressure.

Do not use an impact driver

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS AND TOOL.
SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS.
THE LAST TOOLS YOU WILL EVER NEED TO BUY.

"From the Track... To the Street!"

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-7422



A Division of Thiessen Products

INSTRUCTION SHEET FOR TOOL #2043



FORK NUT SOCKET

USE ON ALL WIDE GLIDE FORK TUBE PLUGS

1. Refer to Harley Davidson® Service Manual for specifications.
2. Remove top fork nut using JIMS® #2244 socket tool.
3. Loosen bottom T-Stem pinch bolt, holding fork tube assembly.
4. Remove fork slider and tube assembly.
5. Carefully clamp tube assembly in vise, using soft jaws, so as not to damage fork tube.
6. **WARNING:** the fork tube plug is under pressure from fork spring. Be careful when removing plug to prevent bodily injury. Unscrew plug slowly, with a 1/2" drive ratchet or breaker bar while applying downward pressure.

Do not use an impact driver

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS AND TOOL.
SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS.
THE LAST TOOLS YOU WILL EVER NEED TO BUY.

"From the Track... To the Street!"

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-7422