


INSTRUCTION SHEET FOR TOOL #6037 ~ #6040



Refer to H-D® Service Manual for specifications about protecting painted surfaces. **CAUTION:** When removing or installing bag latches do not over tighten hardware.

Tools and supplies needed to install latches.

1- Inch lb Torque wrench

1- TORX wrench T15 1- TORX wrench T20 Blue Loctite, used to install studs No. **6046**

1- Wrench or socket 11/32"

PREASSEMBLY

Obtain the 2 studs No. **6046** from the packaging; apply a small drop of blue Loctite to one end of each stud. Install one stud in each latch, threading in until both have bottomed in each hole.

See Fig 1

REMOVAL

- **1.** Before removing bags, use a T15 TORX driver to remove both the outside screws from both bags latch covers. Save all four screws for reinstalling.
- 2. Remove one bag from M/C, with it resting (with the inside facing up) on a pad that is about 12" high. Open the lid (should be facing you) with it resting on a pad. Remove the two # T20 TORX screws holding the "check strap". Fold the strap back to gain access to the two T15 TORX screws holding the key lock. Remove both.
- **3.** At the other end of latch you will find a hex nut. Remove it with your 11/32" tool. This is the last nut holding latch cover to bag hinge so hold cover so it will not fall. Save all hardware for installing new latch covers.
- **4.** Repeat lines 1 thru 3 for the other bag latch.

ASSEMBLY

- 1. Match the latch cover you just removed with one of the new latch covers one is for the right side the other is for the left side.
- **2.** Reverse the removal steps for assembly; only before installing screws apply a small amount of blue Loctite to threads of screws and nut.
- 3. Install all hardware and torque all to 20 in-lbs.



CAUTION: WEAR SAFETY GLASSES OVER YOUR EYE'S.

SEE JIMS® CATALOG FOR HUNDREDS OF TOP QUALITY PROFESSIONAL TOOLS.

THE LAST TOOLS YOU WILL EVER NEED TO BUY.

Performance Parts For Harley-Davidson Motorcycles