

INSTRUCTION SHEET FOR TOOL #985



6-SPEED SHIFT FORK SHAFTS REMOVER TOOL

USE ON ALL 2006 TO PRESENT DYNA AND 2007 TO PRESENT FL & FXST.

Refer to H.D.service manual for the removal of the transmission access door and gear cluster. Place door and gear cluster on a bench with shafts pointed upward. Mark end of shifter shaft so that you can reuse and reinstall in same direction after removing from door. Install remover tool in end of shift fork shaft. These shafts have a slight interference fit. You will need to give the tool a mediun blow with a brass hammer to get tool to lock inside the shaft. Then turn tool in a counterclock wise direction using a 10 mm box end wrench until shaft works loose from door.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS!

SEE JIMS® CATALOG FOR HUNDREDS OF TOP QUALITY PROFESSIONAL TOOLS.

THE LAST TOOLS YOU WILL EVER NEED TO BUY.

Performance Parts For Harley-Davidson Motorcycles

555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-9224

No.985-IS



REV B 3-13

A DIVISION OF THIESSEN PRODUCTS INC.

INSTRUCTION SHEET FOR TOOL #985



6-SPEED SHIFT FORK SHAFTS REMOVER TOOL

Use on all 2006 to present Dyna and 2007 to present FL & FXST.

Refer to H.D.service manual for the removal of the transmission access door and gear cluster. Place door and gear cluster on a bench with shafts pointed upward. Mark end of shifter shaft so that you can reuse and reinstall in same direction after removing from door. Install remover tool in end of shift fork shaft. These shafts have a slight interference fit. You will need to give the tool a mediun blow with a brass hammer to get tool to lock inside the shaft. Then turn tool in a counterclock wise direction using a 10 mm box end wrench until shaft works loose from door.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS! SEE JIMS® CATALOG FOR HUNDREDS OF TOP QUALITY PROFESSIONAL TOOLS.

THE LAST TOOLS YOU WILL EVER NEED TO BUY.

Performance Parts For Harley-Davidson Motorcycles